

526 Micro Tower Workstation



At a Glance

Embedded Compact Design
Professional Design
Intel long life architecture
Extra Cooling
Reliable 24x7 operation
Front & Rear USB 3.0 ports
Heavy duty shipping container



Embedded Micro Tower Workstation

The Model 526-1E embedded computer combines performance with reliability in a compact chassis. The micro chassis provides a variety of mounting orientations to optimize available space. The design combines a high performance chassis with Intel components for enhanced reliability. Product stability is achieved by selecting Intel long life hardware and stable quality branded peripherals. The system has been tested for product safety, emissions, and software compatibility.

DSK3 Standard Features:

Dual Core i3 processor, 8G DDR3 Ram, 500GB HDD, DVD R/W optical drive, 300Watt ATX power supply, 2PCI & 2 PCI express expansion slots, Integrated graphics, audio, and Ethernet, keyboard & Optical mouse. Cover latch for additional security. Front dual & Rear quad USB 3.0 ports, dual serial ports, and dual gigabit Ethernet ports. Heavy Duty shipping container with provisions for materials.

Features:

- High volume CFM fans
- Automatic fan control providing cool and quiet operation
- DVD-R/W
- Space savings



526-1E Specifications

| FEATURE | FUNCTION | DESCRIPTION |
|-------------------|---|--|
| Processor | Socket | 3.3G Hz Intel® Dual Core processor in an LGA1155 socket with 1333 MHz system bus |
| Chipset | | Intel® Q77 |
| Memory | Type Capacity | 8G DDR3 memory 1333Mhz standard and up to 32GB Maximum |
| Video | Controller | Intel® onboard CPU graphics, Dual DVI-I, VGA video, Additional PCI express video slot for alternative video adapters |
| Audio | Controller | Intel® High Definition Audio stereo subsystem |
| | Connectors | Mini Stereo: Line-In, Line-Out, Microphone-In |
| Network | Controller | 10/100/1000 Mbps/sec LAN subsystem using Intel® Gigabit Ethernet controller and Realtek Gigabit controller |
| SATA | Devices Hard Disk Drive CD R/W | 500 GB SATAII, 7200RPM Hard Drive DVD-RW 16x |
| I/O | USB Serial Ports SATA SATA 3.0 | 4 USB 3.0 ports rear I/O and 2 USB front. Two external serial ports 4 SATA 2.0 interfaces with optional raid 2 SATA 3.0 ports up to 6Gb/s |
| Expansion Slots | PCI PCI express | One PCI Conventional* bus add-in card connectors Two PCI Express* x1 bus add-in card connectors One PCI Express* x16 bus add-in card connector |
| System Management | Integrated | Health Monitoring of voltage, temperature and fans 2 system fans and CPU heat sink fan |
| Power Supply | Type Typical | PSU, 300W AC 100W |
| Warranty | | 1 year system; 2 year optional |
| Bays | 3.5" 5.25" | 2 internal (2nd requires optional adapter) 1 external 1 external |
| Weight | | 14 LBS |
| Dimensions | | 13 in 5.4 in 15.5 in |
| Certifications | | CSA60950 Safety, FCC emissions |